



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Brink LED Sconce BRKS Series

Features

Contemporary wall sconce. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture can be mounted horizontally or vertically. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in white or black.

Diffuser

Back lit illumination.

Electrical

This unit is direct wired with a constant current LED driver rated for 120-277V VAC input, 0-10V dimmable.

Lamping

Integrated LED modules capable of producing:
20W = 1600 source lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

White	Black	LED	Source Lumens	CCT	H	W	D
BRKS0424L30D2WH	BRKS0424L30D2BK	20W	1600	3000K	24"	4"	2-3/4"

