



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Maggie LED Ceiling MGGF Series

Features

Decorative ceiling fixture featuring an outer perimeter illuminated edge with a clear bubble acrylic diffuser. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

The canopy is 22-gauge stamped steel. Power supply connections must be made inside a junction box (not included).

Finish

Satin brass or satin nickel.

Diffuser

Clear bubble acrylic diffuser.

Electrical

Input 120 VAC / 60HZ.
Compatible with TRIAC and ELV dimmers.

Lamping

Integrated LED modules capable of producing:
17W = 1700 source lumens, 1200 delivered lumens
34W = 3400 source lumens, 2400 delivered lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.



12"
SB



16"
SN



Ordering Information:

Satin Brass	Satin Nickel	LED	Source Lumens	Delivered Lumens	CCT	DIA.	D
MGGF12L30D1SB	MGGF12L30D1SN	17W	1700	1200	3000K	11-3/4"	3-1/8"
MGGF16L30D1SB	MGGF16L30D1SN	34W	3400	2400	3000K	15-3/4"	3-1/8"