

Casino LED Sconce COS Series

Features

Modern angular overlapping design. Open top and bottom for wall wash effect. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are painted in white or satin nickel.

Diffuser

.100" thick frosted white fabricated acrylic diffuser.

Electrical

This unit is direct wired with a constant current LED driver rated for 120-277V (MV). Compatible with residential (TRIAC/ELV) dimming only at 120VAC.

Lamping

18W = 1300 source lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for damp locations. ADA


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





Ordering Information:

White	Satin Nickel	LED	Source Lumens	сст	Н	w	D
COS6101300L30MVWH	COS6101300L30MVSN	18W	1300	3000K	6-1/2"	10"	3-1/4"
COS6101300L30D1WH	COS6101300L30D1SN	18W	1300	3000K	6-1/2"	10"	3-1/4"