

Hermosa LED Pendant HRP Series

Features

Clear or tinted outer glass pendant is suspended with an 9 foot adjustable cord and can be ordered individual or with a multi-point canopy. Canopy mounts to a standard junction box (not included).

Construction

The glass cylinder is 16" tall and 6" in diameter and held together into place by stem and top cap. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in Satin Nickel.

Diffuser

Glass cylinder pendant is .40" thick. Glass colors include aqua (AQ), clear (CL), clear swirl (CS), and brown (BR).

Electrical

D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.


Lamping

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K and 4000K (CCT). 50,000 hr. LED life, 90 CRI.

Certification

All fixtures are ETL listed for damp locations.

Specifications and dimensions subject to change without notice.








BR Brown

CS Clear Swirl



Ordering Information:

6" DIA. x 16" H

	Source						
Series		LED	CCT	Driver	Finish	Glass	Canopy Options
HRP	1000	L	30 3000K	D1 Voltage (120V TRIAC Dimming)	SN Satin Nickel	AQ Aqua	Blank Monopoint
			40 4000K	D2 Voltage (120-277V 0-10V Dimming)		CL Clear	LNR3 (3) Light Linear
						CS Clear Swirl	RND3 (3) Light Round
						BR Brown	RND6 (6) Light Round

Example: HRP1000L30D1SNAQ