



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

London LED Pendant SLDN Series

Features

Decorative cut metal cylinder pendant is suspended with an 9 ft. adjustable cord.
Product can be used over receptions desks, restaurants, and in public spaces.
Canopy mounts to a standard junction box (not included).

Construction

Hand-blown glass with metal cap. The canopy fits over a standard junction box.
Power supply connections must be made inside a junction box (not included).

Finish

Plated polished nickel.

Diffuser

Hand-blown glass.

Electrical

Input 120 VAC, 60 Hz LED.
LED driver is TRIAC dimmable.

LED

Integrated LED module capable of producing:
7W = 550 lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

| Polished Nickel | LED | Source Lumens | CCT | DIA. | H |
|-----------------|-----|---------------|-------|------|----|
| SLDNP02L1-PN | 7W | 550 | 3000K | 3" | 6" |

