

## Summit LED Sconce SUMS Series

#### **Features**

Dramatic angular design. Indirect light with wall wash effect. Ideal use in hallways, entrances or anywheregeneral lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

#### Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

#### **Finish**

All metal parts are painted in white/silver or black/gold.

#### Diffuser

None

#### **Electrical**

This unit is direct wired with a constant current LED driver rated for 120-277V (MV). Compatible with residential (TRIAC/ELV) dimming only at 120VAC (D1).

#### Lamping

Fixture includes a LED module capable of producing: 14" - 20W = 1300 source lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

#### Certification

All fixtures are cETLus listed for damp locations. ADA


#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

# LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





### **Ordering Information:**

			Source				
White/Silver	Black/Gold	LED	Lumens	CCT	Н	W	D
SUMS051413L30D1WH	SUMS051413L30D1BK	20W	1300	3000K	14"	5"	3"
SUMS051413L30MVWH	SUMS051413L30MVBK	20W	1300	3000K	14"	5"	3"