

CARLSON COLLECTION

Carlson LED 52" Fan Oiled Bronze

300238OLZ (Oiled Bronze)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Airflow

| | |
|------------|------|
| CFM (High) | 6195 |
| CFM (Low) | 1941 |
| RPM (High) | 183 |
| RPM (Low) | 77 |

Certifications/Qualifications

| | |
|-----------------|---|
| Location Rating | CSA UL Listed Dry www.kichler.com/warranty |
|-----------------|---|

Dimensions

| | |
|----------------|-----------------|
| Base Backplate | 6.50 DIA |
| Downrod 1 | 1.00 OD X 4.00" |
| Weight | 29.70 LBS |
| Height | 16.50" |
| Width | 52.00" |

Electrical

| | |
|-------------|--------------|
| Amps (High) | 0.60 |
| Amps (Low) | 0.30 |
| Motor Size | 172MM X 17MM |
| Motor Type | AC |

Mounting/Installation

| | |
|---|-----------|
| Minimum Distance from Fan to 7 feet Floor | |
| Interior/Exterior | Interior |
| Lead Wire Length | 78 |
| Low Ceiling Adaptable | No |
| Mounting Weight | 29.70 LBS |

Photometrics

| | |
|-----------------------|-------|
| Color Rendering Index | 80 |
| Kelvin Temperature | 3000K |

Primary Lamping

| | |
|-----------------------|------------|
| Downward-facing Bulbs | 1X 17W |
| Downlight Included | Yes |
| Downlight Option | Integrated |
| Watts (High) | 71 |
| Watts (Low) | 10 |

Product/Ordering Information

| | |
|--------|--------------|
| SKU | 300238OLZ |
| Finish | Bronze |
| Style | Transitional |
| UPC | 783927543620 |

Specifications

| | |
|----------------------|-------------------|
| Blade Finish 1 | MEDIUM CHERRY |
| Blade Finish 2 | DARK CHERRY |
| Blade Material | WOOD |
| Blade Pitch | 14 |
| Blades Included | Yes |
| Blade Sweep | 52 |
| Diffuser Description | Etched Cased Opal |
| Material | STEEL |
| Max Stem Tilt | 30 Degrees |
| Number of Blades | 5 |
| Blades Reversible | Yes |

Additional Finishes



Antique Pewter



Oiled Bronze

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®