

Hatteras Bay LED 3000K 60" Fan Anvil Iron

310017AVI (Anvil Iron)



Project Name: _____
 Location: _____
 Type: _____
 Qty: _____
 Comments: _____

Airflow

CFM (High)	6282
CFM (Low)	2241
RPM (High)	157
RPM (Low)	65

Certifications/Qualifications

Location Rating	CSA UL Listed Damp www.kichler.com/warranty
-----------------	--

Dimensions

Base Backplate	6.75 DIA
Downrod 1	1.00 OD X 12.00"
Downrod 2 - Measurement A	16.50"
Downrod 2 - Measurement B	12.50"
Downrod 2 - Measurement C	15.25"
Weight	32.50 LBS
Height	17.50"
Width	60.00"

Electrical

Amps (High)	0.60
Amps (Low)	0.28
Motor Size	188MM X 25MM
Motor Type	AC

Mounting/Installation

Minimum Distance from Fan to 7 feet Floor	
Interior/Exterior	Exterior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	32.50 LBS

Photometrics

Color Rendering Index	80
Kelvin Temperature	3000K

Primary Lamping

Dimmable	Yes
Downlight Included	Yes
Downlight Option	Integrated
Lamp Included	Integrated
Light Source	LED
# of Bulbs/LED Modules	1
Watts (High)	71
Watts (Low)	17

Product/Ordering Information

SKU	310017AVI
Finish	Antique/Burnished
Style	Traditional
UPC	783927600149

Specifications

Blade Finish 1	WALNUT
Blade Finish 2	DIST ANTIQ GREY
Blade Material	ABS
Blade Pitch	12
Blades Included	Yes

Blade Sweep	60
Diffuser Description	Fresnel Lens
Material	STEEL
Max Stem Tilt	22 Degrees
Number of Blades	5
Blades Reversible	Yes
Wall Control Included	Yes

Additional Finishes



Anvil Iron



Distressed Black



Weathered Zinc

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®