# Sutter Place Select LED 2700K 52" Fan Matte White

339501MWH (Matte White)

Project Name:	
Location:	
Type:	
Qty:	
Comments:	

### Airflow

AIIIIOW		
CFM (High)	3832	
CFM (Low)	1598	
RPM (High)	152	
RPM (Low)	70	

### Certifications/Qualifications

Location Rating	CSA UL Listed Dry
	www.kichler.com/warranty

### Dimensions

Base Backplate	5.25 DIA
Downrod 1	1.00 OD X 4.00"
Downrod 2 - Measurement A	15.25"
Downrod 2 - Measurement B	8.00"
Downrod 2 - Measurement C	12.00"
Downrod 2	FLUSH MOUNT"
Weight	18.61 LBS
Height	18.00"
Width	52.00"

## Electrical

Amps (High)	0.42
Amps (Low)	0.23
Motor Size	152 MM X 15 MM
Motor Type	ACINDUCTION

## Mounting/Installation

Minimum Distance from Fan to 7 feet

Floor	
Interior/Exterior	Interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	18.61 LBS

### **Photometrics**

Color Rendering Index	80
Kelvin Temperature	2700K

#### **Primary Lamping**

Downlight Included	Yes
Downlight Option	Removable
Lamp Included	Included
Lamp Type	E12
Light Source	LED
# of Bulbs/LED Modules	3
Socket Type	CAND
Watts (High)	49
Watts (Low)	11

### Product/Ordering Information

SKU	339501MWH	
Finish	White	
Style	Traditional	
UPC	783927600378	


# Specifications

Specifications	
Blade Finish 1	MATTE WHIITE
Blade Material	WOOD
Blade Pitch	12



Blades Included	Yes
Blade Sweep	52
Diffuser Description	White Alabaster
Material	STEEL, PLYWOOD, GLASS
Max Stem Tilt	22 Degrees
Number of Blades	5

### **Additional Finishes**



#### Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

#### Notes:

Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference column.

. only.

