

Project Name

Location

Prepared By

SATCO S11411

9.5A19/LED/950/120V/90CRI/10PK

Notes

General	
Status	Active
Watts	9.5
Incandescent Equivalent	60
Volts	120V
Shape	A19
Base	Medium
ANSI Base	E26
Finish	Frosted
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	90
Lumens	760
Beam Spread	220
Dimmable	Non-Dimmable
Hours Rated	10000
Lamp Type	А-Туре
Technology	LED
Electrical	
Operating Frequency	60 Hz
Dimming Type	N/A
Diffining Type	IV/A
Power Factor	0.81
Power Factor Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
	-20C (-4F) to a maximum of +45C
Operating Temperature Physical	-20C (-4F) to a maximum of +45C (+113F)
Operating Temperature Physical MOL	-20C (-4F) to a maximum of +45C (+113F)
Operating Temperature Physical MOL MOD	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38
Operating Temperature Physical MOL MOD Housing Color	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White
Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38
Operating Temperature Physical MOL MOD Housing Color	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White
Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging.
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging. Enclosed Rated Lamp
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info Enclosure Rating Warranty	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging. Enclosed Rated Lamp
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info Enclosure Rating Warranty Compliance	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging. Enclosed Rated Lamp 3 Year Limited - 10 hr per day
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info Enclosure Rating Warranty Compliance Safety Listing	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging. Enclosed Rated Lamp 3 Year Limited - 10 hr per day
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Additional Info Enclosure Rating Warranty Compliance Safety Listing Location Rating	-20C (-4F) to a maximum of +45C (+113F) 4.41 2.38 White 0.14 Designed for 15000 hours. Due to Energy Star filing requirements the hours are under-stated at 10000 hours on the packaging. Enclosed Rated Lamp 3 Year Limited - 10 hr per day cULus Damp











