## SATCO NUVO

Project Name

Location

Prepared By



M	$\overline{}$	-	•

General	
Status	Active
Watts	9.5
Incandescent Equivalent	60
Fluorescent Equivalent	13
Volts	120V
Shape	A19
Base	Medium
ANSI Base	E26
Finish	Frosted White
CCT (Kelvin)	4000
Temperature	Cool White
CRI	84
Lumens	800
Beam Spread	220
Dimmable	Non-Dimmable
Hours Rated	15000
Lamp Type	Туре А
Technology	LED
Electrical	
Dimming Type	N/A
Dimming Type Power Factor	N/A 0.6
Power Factor	0.6 -25C (-13F) to a maximum of +45C
Power Factor  Operating Temperature	0.6 -25C (-13F) to a maximum of +45C
Power Factor Operating Temperature Physical	0.6 -25C (-13F) to a maximum of +45C (+113F)
Power Factor Operating Temperature Physical MOL	0.6 -25C (-13F) to a maximum of +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38
Power Factor Operating Temperature  Physical MOL MOD  Additional Information Additional Info Enclosure Rating	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture  Warranty	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture  Warranty  Compliance	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes 3 Year Limited - 10 hr per day
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture Warranty  Compliance  Safety Listing Location Rating	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes 3 Year Limited - 10 hr per day
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture Warranty  Compliance  Safety Listing	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes 3 Year Limited - 10 hr per day  cULus Damp
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture Warranty  Compliance  Safety Listing Location Rating Energy Star	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes 3 Year Limited - 10 hr per day  cULus Damp Yes
Power Factor Operating Temperature  Physical  MOL  MOD  Additional Information  Additional Info Enclosure Rating Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating Energy Star ES Unique ID	0.6 -25C (-13F) to a maximum of +45C (+113F)  4.31 2.38  Solid State LED lighting Enclosed Rated Lamp Yes 3 Year Limited - 10 hr per day  cULus Damp Yes ESID-2318798





LED\_Lamp





SDS Sheet