SATCO NUVO

Project Name

Location Prepared By



M	$\overline{}$		۰
	L D	(-1	-

Active
1.6
12V
Т3
Bi Pin G4
G4
Clear
3000
Warm White
80
200
360
Yes Dimmable
25000
Miniature
LED
LED
-20C (-4F) to a maximum of +45C (+113F)
-20C (-4F) to a maximum of +45C
-20C (-4F) to a maximum of +45C
-20C (-4F) to a maximum of +45C (+113F)
-20C (-4F) to a maximum of +45C (+113F)
-20C (-4F) to a maximum of +45C (+113F)
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp 3 Year Limited
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp 3 Year Limited cETLus
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp 3 Year Limited cETLus Damp
-20C (-4F) to a maximum of +45C (+113F) 1.44 0.38 Enclosed Rated Lamp 3 Year Limited cETLus Damp No







